KB ADHESIVES CO., LTD.
Office : Rm. 402, Nene Bldg., 391 Nohae-ro, Dobong-gu, Seoul, Korea
Tel : +82 2 905 7864 Fax : +82 2 905 7867 www.kbadhesves.com
Factory : 32-12, Geumgyedong-gil, Hwaseong-myeon, Cheongyang-gun, Chungcheongnam-do, Korea

KB22038(Perm/ Peel Double Sided PET Tape)

Description

D2038 is a dual coated PET double sided tape, which allows permanent fixing to one surface and a removable (peelable) surface on the reverse side, permanent adhesive on the open (exposed) side and peelable adhesive on the liner side. It has very good electrical insulation and temperature resistance. Widely apply on window displays, posters and notice boards, where repeat/ temporary fixation is required.

Composition

110g/㎡Double-side PE coated Release Paper
Solvent Base Acrylic Adhesive
PET
Solvent Base Acrylic Adhesive

Technical Characteristics

Item No.	D2038
Tape Thickness, mm (±0.005)	0.090
Carrier Material/ thickness, mm	0.025mm, Polyester
Colour	Transparent
Adhesion to Steel, N/ 25mm (removable side)	≤4
Adhesion to Steal, N/ 25mm (permanent side)	>15
Tack, Ball Number # (removable side)	7
Tack, Ball Number # (permanent side)	10
Holding Power, hr/25mm×25mm/kg, (permanent side)	>24

Standard Size

Width	Length
960mm	50m

Available in other sizes as well.

**The above mentioned data represents the average obtained in our laboratory. Suggestions for use and final results correspond to our best Technical experience but cannot be intended as our commitment or liability. The user shall determine the suitability of the product and the method of application for each special use.