

DOUBLE SIDED PE Foam Tape KBPP280

► Product Description


Double Sided PE Foam Tape Series is PE foam by double coated with modified solvent acrylic adhesive, has strong ultimate bonding, high shear strength and low and high service temperature ability

► Technical Data

Test standard	China GB	ASTM	FINAT	JIS
Tape Thickness(mm)	0.93			
Color	Black/White			
Adhesion Power	20N/25mm	20N/25mm	20N/25mm	20N/25mm
Initial Tack	16#(ball)	3cm	16N/25mm	16#(ball)
Holding Power	>200 hours	>200 hours	>200 hours	>200 hours

► Application

Used for long-terms bonding trims and profiles affixing room & car mirrors, window bars, mounting cable clips and cable covers, even on rough surfaces.



► Construction



Modified Solvent base Acrylic Adhesive
Polyethylene foam, 0.8mm
Modified Solvent base Acrylic Adhesive
Brown silicone liner 90g/m²

► Temperature

Application (Minimum): 10 °C
Service (long term): -30 °C to 100 °C
Short term: 120 °C

► Standard Size

	Tape width	Usable width	Length
Jumbo rolls	1070mm	1040mm	100M, 200M
Log rolls	1070mm	1040mm	20M

► Surface Preparation

It is essential, as with all pressure sensitive tapes, that the surface to which the tape is applied be clean, dry and free of grease and oil

► Storage and Shelf Life

The shelf life of the products is one years when stored at 18-25 °C, 30-70% relative humidity and out of direct sunlight, in good packaging.