

KB ADHESIVES CO., LTD.



Office : Rm. 402, Nene Bldg., 391 Nohae-ro, Dobong-gu, Seoul, Korea

Tel : +82 2 905 7866 Fax : +82 2 905 7867 www.kbadhesves.com

Factory : 32-12, Geumgyedong-gil, Hwaseong-myeon, Cheongyang-gun, Chungcheongnam-do, Korea



POM 300 Foam Tape

Description

PO300 is grey color Polyolefin foam, very soft and flexible carrier, coated with modified solvent acrylic adhesive, excellent adhesion and high shear strength. Apply on helmet processing, car audio fixing, IT products framework etc.

Composition

Red / Green PE Release Film
Modified Solvent Based Acrylic Adhesive
PO Foam 0.2 mm
Modified Solvent Based Acrylic Adhesive

Technical Characteristics

Item No.	POM300
Tape Thickness , mm	0.300
Material carrier	Polyolefin Foam
Colour	Grey
Adhesion to Steel, N/25mm	>25
Tack, Ball Number	15
Holding Power, hr/kg/10mm/25°C	168
Holding Power, hr/kg/25mm/80°C	24

Standard Size

Width	Length
1000mm	50m

Available in other sizes as well.

**The above mentioned data represents the average obtained in our laboratory. Suggestions for use and final results correspond to our best Technical experience but cannot be intended as our commitment or liability. The user shall determine the suitability of the product and the method of application for each special use.