

Non Woven Double Sided Tape LT1440

► Product Description

Superior adhesive strength, permanent mount, can be curved, repulsion.
High adhesion to wide range of materials(like plastic, metal...)
Good season resistant, low and high service temperature ability

► Technical Data

Test standard	China GB	ASTM	FINAT	JIS
Tape Thickness(mm)	0.4			
Color	Translucent			
Adhesion Power	20N/25mm	20N/25mm	20N/25mm	20N/25mm
Initial Tack	16#(ball)	3cm	20N/25mm	16#(ball)
Holding Power	>100 hours	>100 hours	>100 hours	>100 hours

► Application

Bonding punched metal or plastic nameplates, and fixing plastic display panel (like automobile meter panels and air-conditioners), and also permanent laminating household electric appliances components and parts.



► Construction



Modified Solvent base Acrylic Adhesive
Non-woven g/m2
Modified Solvent base Acrylic Adhesive
PE paper release liner 115g/m2(with print LUXKING)

► Temperature

Application (Minimum): 10 °C
Service (long term): -20 °C to 120 °C
Short term: 180 °C

► Standard Size

	Tape width	Usable width	Length
Jumbo rolls	1260mm	1220mm	500, 700, 1000M
Log rolls	1260mm	1220mm	50, 100M

► Surface Preparation

It is essential, as with all pressure sensitive tapes, that the surface to which the tape is applied be clean, dry and free of grease and oil

► Storage and Shelf Life

The shelf life of the products is one year when stored at 18-25 °C, 30-70% relative humidity and out of direct sunlight, in good packaging.