

## Double Sided Tissue Tape KB2501F

### ► Product Description

D501F is a high performance tissue carrier double-sided tape with excellent adhesion, good holding power, excellent temperature resistance and repulsion resistance. Design application on Rice-Cooker, Refrigerator, Temperature Controller Heater for heating component lamination.

### ► Technical Data

Test standard	China GB	ASTM	FINAT	JIS
Tape Thickness(mm)	0.14			
Color	Translucent			
Adhesion Power	15N/25mm	15N/25mm	15N/25mm	15N/25mm
Initial Tack	13#(ball)	.	.	13#(ball)
Holding Power	>100 hours	>100 hours	>100 hours	>100 hours

### ► Construction



Modified solvent base acrylic adhesive  
Tissue 14g/m<sup>2</sup>  
Modified solvent base acrylic adhesive  
PE paper release liner 110g/m<sup>2</sup>



### ► Temperature

Service (long term): -20℃ to 150℃  
Short term: 200℃

### ► Standard Size

	Tape width	Usable width	Length
Jumbo rolls	1040, 1260mm	1020, 1240mm	500, 700, 1000M
Log rolls	1040, 1260mm	1020, 1240mm	50, 100M

### ► Surface Preparation

It is essential, as with all pressure sensitive tapes, that the surface to which the tape is applied be clean, dry and free of grease and oil

### ► Storage and Shelf Life

The shelf life of the products is one years when stored at 18-25℃, 30-70% relative humidity and out of direct sunlight, in good packaging.