

## Double Sided Tissue Tape KB2600

### ► Product Description

Superior adhesive strength, permanent mount, can be curved, repulsion.  
High adhesion to wide range of materials(like plastic, metal...)  
Good season resistant, low and high sevice temperautre ability

### ► Technical Data

Test standard	China GB	ASTM	FINAT	JIS
Tape Thickness(mm)	0.16			
Color	Translucent			
Adhesion Power	17N/25mm	17N/25mm	17N/25mm	17N/25mm
Initial Tack	15#(ball)	3cm	16N/25mm	16#(ball)
Holding Power	>72 hours	>72 hours	>72 hours	>72 hours

### ► Application

Bonding punched metal or plastic nameplates, and fixing plastic disply panel (like automobile meter panels and air-conditioners), and also permanent laminating household electric appliances components and parts.



### ► Construction



Modified solvent base acrylic adhesive  
Tissue 14g/m2  
Modified solvent base acrylic adhesive  
PE paper release liner 115g/m2(with print LUXKING)

### ► Temperature

Application (Minimum): 10 °C  
Service (long term): -20 °C to 120 °C  
Short term: 180 °C

### ► Standard Size

	Tape width	Usable width	Length
Jumbo rolls	1040, 1260mm	1020, 1240mm	500, 700, 1000M
Log rolls	1040, 1260mm	1020, 1240mm	50, 100M

### ► Surface Preparation

It is essential, as with all pressure sensitive tapes, that the surface to which the tape is applied be clean, dry and free of grease and oil

### ► Storage and Shelf Life

The shelf life of the products is one years when stored at 18-25 °C, 30-70% releative humidity and out of direct sunlight, in good packaging.